



Characteristics

Black Colour
RoHS Compliant
REACH Compliant



Typical Applications

Binding of Neutral Screen Wires and Tapes and Wire Armouring
Under/Over Corrugated Metal Tape
Conductor Peripheral Wrap
Multi Core Cable Binding

Benefits

Proven Long Term Stability
Prevents Extruded Compound Penetration
Excellent Flexibility and Bi-directional Tensile Strength

Typical Properties (T = 23°C - RH = 50%)

	GFS5611	Unit	Test Method
Mass per Unit Area	117	g/m ²	ISO-9073-1
Thickness	0.26	mm	ISO-9073-2
Tensile Strength	135	N/cm	ISO-9073-3
Elongation	24	%	ISO-9073-3
Swelling Speed	2.5	mm/1'00"	GTEST20*
Swelling Height	3.5	mm/2'00"	GTEST20*
Surface Resistance	500	Ω/□	IEC-167
Volume Resistance	0.1	MΩ.cm	DIN-54345
Maximum Processing Temperature	230	°C	GTEST12*
Maximum Service Temperature	145	°C	IEC-216

*Geca-Tapes test method

Packaging

Typical Minimum Slit Width	9 mm
Standard Core Inside Diameter	76 mm
Pad Outside Diameter	Various
Traverse Wound Spool Available	YES

Other packaging combinations available. Please contact Geca-Tapes for details.

Storage & Handling Recommendations

Optimum storage conditions: T = 18-28°C, RH ≤ 50%

Protect material from dust, humidity, heat, liquids

Store material in original, sealed packaging when not used

See Info Sheet GIS006 available from our website for further information on storage, handling, processing and warranty.

Ordering Information

When ordering, please specify slit width, inner diameter and maximum outside diameter.

PGI Geca-Tapes, ZI de la Blanche Maison, Avenue des Nations Unies, BP 109, 59270 Bailleul, FRANCE

T +33(0)3 28 43 74 74 | F +33(0)3 28 43 74 63 | info@geca-tapes.com | www.geca-tapes.com

Technical Support

Geca-Tapes will help you through your design process until the most suitable waterblocking solution is selected and proven successful, and can advise on a wide range of topics related to waterblocking tapes and yarns processing.

Please see the Information Sheets available from our website for further information and typical applications for this product or contact us at techinfo@geca-tapes.com.